



JERIC

Tongue & Groove Hardwood Adhesive

❖ Environmentally Safe
For Floating Floor and
Engineered Hardwood
Tongue and Groove
Applications

Tongue and Groove Adhesive

<p>Description</p>	<p>Tongue & Groove Hardwood Adhesive is water-based, non-flammable, non-toxic and is designed to bond engineered hardwood and laminated flooring together at tongue and groove when laying a floating floor system. Meets Type II/D3 water resistance specifications.</p>
<p>Application</p>	<p>Ensure that the adhesive and flooring products to be used are acclimatized to the temperature of the room where they will be installed.</p> <ol style="list-style-type: none"> 1. Follow the flooring manufacturer's instructions. 2. Apply a continuous bead of adhesive 3mm (1/8") minimum to the top inside of all panel grooves (sides and ends). 3. Fit the panels together tightly, using a tapping block to ensure maximum adhesive distribution and adequate bond. 4. Wipe off any excess adhesive that has been squeezed out between the joints with a clean, damp cloth. If adhesive dries on surface, use R&D DeZolve 10 adhesive remover to remove. 5. Allow glue to cure for approximately 24 hours at 21°C (70°F) before subjecting floor to heavy traffic.
<p>Coverage</p>	<p>Approximately 120 metres (400 linear feet) of a 3mm (1/8") bead per 473ML bottle.</p>